

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 001  
Date Prepared: 01-14-02  
Date Printed: 12/05/03  
MSDS No: 0178051-010.002

Parts Master HD SAE 40

---

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: Parts Master HD SAE 40

General or Generic ID: PETROLEUM BASED-LUBRICATING OIL

Company

The Valvoline Company  
P.O. Box 14000  
Lexington, KY 40512

Telephone Numbers

Emergency: 1-800-274-5263  
Information: 1-859-357-7206

---

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by weight)
ALIPHATIC PETROLEUM DISTILLATES	64742-65-0	84.0- 94.0
DETERGENT/DISPERSANT ENGINE OIL PACKAGE		6.0- 16.0
ZINC COMPOUNDS	68649-42-3	1.1- 1.1

---

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

May cause mild eye irritation.

Skin

May cause mild skin irritation. Prolonged or repeated contact may dry and crack the skin.

Swallowing

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

Continued on next page

The Valvoline Company

Page 002

Date Prepared: 01-14-02

Date Printed: 12/05/03

MSDS No: 0178051-010.002

Parts Master HD SAE 40

---

Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Symptoms usually occur at air concentrations higher than the recommended exposure limits (See Section 8).

Symptoms of Exposure

stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), pain in the abdomen.

Target Organ Effects

No data

Developmental Information

No data

Cancer Information

Used motor oil has been shown to cause skin cancer in laboratory animals continually exposed by repeated applications. Avoid prolonged or repeated skin contact.

Other Health Effects

No data

Primary Route(s) of Entry

No data

---

4. FIRST AID MEASURES

Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Continued on next page

The Valvoline Company

Page 003

Date Prepared: 01-14-02

Date Printed: 12/05/03

MSDS No: 0178051-010.002

Parts Master HD SAE 40

---

Swallowing

Do not induce vomiting. Give one glass of milk or water, and get medical attention immediately. If possible, do not leave victim unattended.

Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

Note to Physicians

Preexisting disorders of the following organs ( or organ systems) may be aggravated by exposure to this material: skin.

---

5. FIRE FIGHTING MEASURES

Flash Point

440.0 F (226.6 C)

Explosive Limit

No data

Autoignition Temperature

No data

Hazardous Products of Combustion

May form: carbon dioxide and carbon monoxide, oxides of sulfur, nitrogen and phosphorus, various hydrocarbons.

Fire and Explosion Hazards

Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Dense smoke may be generated while burning.

Extinguishing Media

regular foam, carbon dioxide, dry chemical.

Continued on next page

The Valvoline Company

Page 004  
Date Prepared: 01-14-02  
Date Printed: 12/05/03  
MSDS No: 0178051-010.002

Parts Master HD SAE 40

---

**Fire Fighting Instructions**

Water or foam may cause frothing which can be violent and possibly endanger the life of the firefighter. Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

**NFPA Rating**

Health - 1, Flammability - 1, Reactivity - 0

---

**6. ACCIDENTAL RELEASE MEASURES**

**Small Spill**

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

**Large Spill**

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source, dike area of spill to prevent spreading, pump liquid to salvage tank. Remaining liquid may be taken up on sand, clay, earth, floor absorbent, or other absorbent material and shoveled into containers.

---

**7. HANDLING AND STORAGE**

**Handling**

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

Continued on next page



Parts Master HD SAE 40

---

Storage  
Not applicable

---

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Not required under normal conditions of use. However, if misting or splashing conditions exist, then safety glasses or chemical splash goggles are advised.

Skin Protection

Not normally required. However, wear resistant gloves such as nitrile rubber to prevent irritation which may result from prolonged or repeated skin contact with product., Wear normal work clothing covering arms and legs..

Respiratory Protections

Not required under normal conditions of use. However, if oil mists are generated above recommended PEL/TLV of 5 mg/m<sup>3</sup>, then a NIOSH/MSHA approved respirator is advised in absence of proper environmental control. (See your industrial hygienist.)

Engineering Controls

Not required under normal conditions of use. However, if unusual operating conditions exist, then provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below PEL/TLV (s).

Exposure Guidelines

Component  
-----

ALIPHATIC PETROLEUM DISTILLATES (64742-65-0)  
OSHA VPEL 5.000 mg/m<sup>3</sup> - TWA Oil Mist  
ACGIH TLV 5.000 mg/m<sup>3</sup> - TWA Oil Mist

DETERGENT/DISPERSANT ENGINE OIL PACKAGE  
No exposure limits established

ZINC COMPOUNDS (68649-42-3)  
No exposure limits established

Continued on next page

Parts Master HD SAE 40

---

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point  
(for component) > 425.0 F (218.3 C) @ 760.00 mmHg

Vapor Pressure  
No data

Specific Vapor Density  
No data

Specific Gravity  
.893 @ 60.00 F

Liquid Density  
7.440 lbs/gal @ 60.00 F  
.893 kg/l @ 15.60 C

Percent Volatiles (Including Water)  
No data

Evaporation Rate  
No data

Appearance  
DRY, CLEAR & BRIGHT

State  
LIQUID

Physical Form  
No data

Color  
No data

odor  
No data

Continued on next page

Parts Master HD SAE 40

---

pH

No data

Viscosity

13.5 - 15.5 cst

---

#### 10. STABILITY AND REACTIVITY

Hazardous Polymerization

Product will not undergo hazardous polymerization.

Hazardous Decomposition

May form: carbon dioxide and carbon monoxide, oxides of sulfur, nitrogen and phosphorus, various hydrocarbons.

Chemical Stability

Stable.

Incompatibility

Avoid contact with: strong oxidizing agents.

---

#### 11. TOXICOLOGICAL INFORMATION

No data

---

#### 12. ECOLOGICAL INFORMATION

No data

---

#### 13. DISPOSAL CONSIDERATION

Waste Management Information

Dispose of in accordance with all applicable local, state and federal regulations.

Continued on next page

Parts Master HD SAE 40

---

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:  
Not Regulated

Container/Mode:  
CASES/SURFACE - NO EXCEPTIONS

NOS Component:  
None

RQ (Reportable Quantity) - 49 CFR 172.101  
Not applicable

---

15. REGULATORY INFORMATION

US Federal Regulations

CERCLA RQ - 40 CFR 302.4  
None

SARA 302 Components - 40 CFR 355 Appendix A  
None

Section 311/312 Hazard Class - 40 CFR 370.2  
Immediate( ) Delayed( ) Fire( ) Reactive( ) Sudden  
Release of Pressure( )

SARA 313 Components - 40 CFR 372.65

Section 313 Component(s)	CAS Number
ZINC C1-C14 ALKYL DITHIOPHOSPHATE	68649-42-3

International Regulations

Inventory Status  
Not determined

Continued on next page

The Valvoline Company

Page 009

Date Prepared: 01-14-02

Date Printed: 12/05/03

MSDS No: 0178051-010.002

Parts Master HD SAE 40

---

State and Local Regulations  
California Proposition 65  
None

---

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

Last page